



TYPE 2 ARMoured INSTRUMENTATION PVC CAT CABLE



APPLICATION

Manufactured to PAS5308, Instrumentation cables are intrinsically safe and designed for use in communication and instrumentation applications in and around process industries for transmission of signals in control systems. The signals can be analogue or digital from a variety of sensors and transducers.

CABLE STANDARDS

Flame propagation to BS4066 Pt 1 & 3
 PAS5308
 BS 50265
 BS EN 50266
 BS EN/IEC 60332-3-24

CONSTRUCTION PART 1

Conductor: Plain Annealed Copper Conductors
Insulation: Polyethylene (PET) Laid up to form pairs
Screen: Collective aluminium / mylar tape screen complete with 0.5mm drain wire
Bedding: Polyethylene (PET)
Armour: Galvanised Steel Wire
Sheath: Polyvinyl Chloride (PVC)
Sheath Colour: Blue or Black

CONSTRUCTION PART 2

Conductor: Plain Annealed Copper Conductors
Insulation: Polyvinyl Chloride (PVC)
 Laid up to form pairs
Tape: Collective aluminium / mylar tape screen complete with 0.5mm drain wire
Bedding: Polyvinyl Chloride (PVC)
Armour: Galvanised Steel Wire
Sheath: Polyvinyl Chloride (PVC)
Sheath Colour: Blue or Black (**available in Green)

CHARACTERISTICS

Voltage Rating: 300/500 Volts
Temperature Limits: -20°C to +65°C
Minimum Bending Radius: As per cable manufacturer datasheet

CORE IDENTIFICATION

For Part 1 cables: Refer to Part 1 colour chart on page 3
For Part 2 Cables: Refer to Part 2 colour chart on page 3

PAS 5308 TYPE 2 ARMOURED PVC CAT CABLE - DIMENSIONS

CCC CODE		CONDUCTOR SIZE (MM ²)	STRANDING (MM)	NO OF PAIRS	WEIGHT (KG/KM)	OVERALL DIAMETER	GLAND SIZE
PART 1	PART 2						
7118	7318	0.5	16/0.20	1	242	10.8	20/16
7119	7319	0.5	16/0.20	2	288	11.7	20S
7120	7320	0.5	16/0.20	5	535	17.3	20
7121	7321	0.5	16/0.20	10	868	22.3	25
7122	7322	0.5	16/0.20	20	1466	28.5	32
7123	7323	0.5	16/0.20	30	1944	33.3	32
7124	7324	0.5	16/0.20	50	3360	41.5	50S
7125	7325	0.5	16/0.20	1 Triple	259	11	20/16
7155	7355	0.75	24/0.20	1	270	11.1	20/16
7156	7356	0.75	24/0.20	2	330	12.3	20S
7157	7357	0.75	24/0.20	5	719	19.2	20
7158	7358	0.75	24/0.20	10	1150	24.7	25
7159	7359	0.75	24/0.20	20	1704	30.7	32
7160	7360	0.75	24/0.20	30	2570	36.9	40
7161	7361	0.75	24/0.20	50	4400	46.4	50S
7162	7362	0.75	24/0.20	1 Triple	288	11.4	20S
**7231	-	1	1/1.13	1	250	11.8	20/16
**7232	-	1	1/1.13	2	300	13	20S
**7233	-	1	1/1.13	5	560	19.7	20
**7234	-	1	1/1.13	10	970	24.3	25
**7235	-	1	1/1.13	20	1240	31.2	40
**7236	-	1	1/1.13	30	2180	36.2	50S
**7237	-	1	1/1.13	50	3500	45.7	50
7189	7389	1.5	7/0.53	1	312	12.3	20S
7190	7390	1.5	7/0.53	2	397	13.7	20S
7191	7391	1.5	7/0.53	5	918	21.5	25
7192	7392	1.5	7/0.53	10	1466	27.8	32
7193	7393	1.5	7/0.53	20	2519	35.1	40
7194	7394	1.5	7/0.53	30	3352	41.9	50S
7195	7395	1.5	7/0.53	50	5310	53.4	63S
7196	7396	1.5	7/0.53	1 Triple	357	12.6	20S
7208	7408	2.5	7/0.67	1	395	13.1	20S
7209	7409	2.5	7/0.67	2	490	15.9	20
7210	7410	2.5	7/0.67	5	1430	26.5	20
7211	7411	2.5	7/0.67	10	2235	35.1	40
7212	7412	2.5	7/0.67	20	3935	46.7	50
7213	7413	2.5	7/0.67	1 Triple	407	13.7	20S

PAS 5308 TYPE 2 PVC CAT CABLE – CONDUCTOR RESISTANCE

NOMINAL CROSS SECTIONAL AREA (MM ²)	CONDUCTOR CLASS	MAXIMUM RESISTANCE CONDUCTOR AT 20°C Ω/KM
0.5	5	39
0.75	5	26
1	1	18.1
1.5	2	12.1
2.5	2	7.41

THE ABOVE IS IN ACCORDANCE WITH 18TH EDITION OF IET WIRING REGULATIONS

PAS 5308 TYPE 2 – CURRENT CAPACITY

NOMINAL CROSS SECTIONAL AREA (MM ²)	MUTUAL CAPACITANCE pF/m			MINIMUM INSULATION RESISTANCE AT 20°C MOHMS/KM	MAXIMUM L/R RATIO MH/OHMS
	CABLES WITH COLLECTIVE SCREEN ONLY	1 PAIR, 2 PAIRS, 1 TRIPLE COLLECTIVELY SCREENED	CABLES WITH INDIVIDUALLY SCREENED PAIRS		
0.5	75	115	115	>5	25
0.75	75	115	115	>5	25
1	75	115	115	>5	25
1.5	85	120	120	>5	40
2.5	85	120	120	>5	65

THE ABOVE IS IN ACCORDANCE WITH 18TH EDITION OF IET WIRING REGULATIONS

PAS 5308 INSTRUMENT CABLE - PAIR COLOUR CHARTS

PART 1 PAIR COLOURS					
PAIR	A	B	PAIR	A	B
1	BLACK	BLUE	26	WHITE	YELLOW
2	BLACK	GREEN	27	RED	YELLOW
3	BLUE	GREEN	28	ORANGE	YELLOW
4	BLACK	BROWN	29	BLACK	GREY
5	BLUE	BROWN	30	BLUE	GREY
6	GREEN	BROWN	31	GREEN	GREY
7	BLACK	WHITE	32	BROWN	GREY
8	BLUE	WHITE	33	WHITE	GREY
9	GREEN	WHITE	34	RED	GREY
10	BROWN	WHITE	35	ORANGE	GREY
11	BLACK	RED	36	YELLOW	GREY
12	BLUE	RED	37	BLACK	VIOLET
13	GREEN	RED	38	BLUE	VIOLET
14	BROWN	RED	39	GREEN	VIOLET
15	WHITE	RED	40	BROWN	VIOLET
16	BLACK	ORANGE	41	WHITE	VIOLET
17	BLUE	ORANGE	42	RED	VIOLET
18	GREEN	ORANGE	43	ORANGE	VIOLET
19	BROWN	ORANGE	44	YELLOW	VIOLET
20	WHITE	ORANGE	45	GREY	VIOLET
21	RED	ORANGE	46	BLACK	TURQUOISE
22	BLACK	YELLOW	47	BLUE	TURQUOISE
23	BLUE	YELLOW	48	GREEN	TURQUOISE
24	GREEN	YELLOW	49	BROWN	TURQUOISE
25	BROWN	YELLOW	50	WHITE	TURQUOISE

PART 2 PAIR COLOURS					
PAIR	A	B	Pair	A	B
1	WHITE	BLUE 2	6	RED/BLUE	BLUE
2	WHITE	ORANGE	27	RED/BLUE	ORANGE
3	WHITE	GREEN	28	RED/BLUE	GREEN
4	WHITE	BROWN	29	RED/BLUE	BROWN
5	WHITE	GREY	30	RED/BLUE	GREY
6	RED	BLUE	31	BLUE/BLACK	BLUE
7	RED	ORANGE	32	BLUE/BLACK	ORANGE
8	RED	GREEN	33	BLUE/BLACK	GREEN
9	RED	BROWN	34	BLUE/BLACK	BROWN
10	RED	GREY	35	BLUE/BLACK	GREY
11	BLACK	BLUE	36	YELLOW/BLUE	BLUE
12	BLACK	ORANGE	37	YELLOW/BLUE	ORANGE
13	BLACK	GREEN	38	YELLOW/BLUE	GREEN
14	BLACK	BROWN	39	YELLOW/BLUE	BROWN
15	BLACK	GREY	40	YELLOW/BLUE	GREY
16	YELLOW	BLUE	41	WHITE / ORANGE	BLUE
17	YELLOW	ORANGE	42	WHITE/ ORANGE	ORANGE
18	YELLOW	GREEN	43	WHITE / ORANGE	GREEN
19	YELLOW	BROWN	44	WHITE / ORANGE	BROWN
20	YELLOW	GREY	45	WHITE / ORANGE	GREY
21	WHITE/BLUE	BLUE	46	ORANGE/RED	BLUE
22	WHITE/BLUE	ORANGE	47	ORANGE/RED	ORANGE
23	WHITE/BLUE	GREEN	48	ORANGE/RED	GREEN
24	WHITE/BLUE	BROWN	49	ORANGE/RED	BROWN
25	WHITE/BLUE	GREY	50	ORANGE/RED	GREY

- FOR INDIVIDUAL SCREENED PAIRS, IDENTIFICATION WILL BE BLACK/BLUE NUMBERED PAIRS.
- TWO PAIR COLLECTIVELY SCREENED CABLES ARE IN QUAD FORMATION COLOUR CODED IN ROTATION, BLACK, BLUE, GREEN, BROWN.
- SINGLE TRIPLE WILL BE BLUE , BLACK, GREEN
- FOR INDIVIDUAL SCREENED PAIRS, IDENTIFICATION WILL BE WHITE/BLUE NUMBERED PAIRS.
- TWO PAIR COLLECTIVELY SCREENED CABLES ARE IN QUAD FORMATION COLOUR CODED IN ROTATION, BLACK, BLUE, GREEN, BROWN
- SINGLE TRIPLE WILL BE BLUE, WHITE, ORANGE.