

CJC® Filter Insert, type PSi

Specially designed for filtration of wash oils

CJC® PSi FILTER INSERTS

The CJC® PSi Filter Insert is a Pressure Stamping Filter Insert used for cleaning wash oil for metal sheets prior to forming e.g. car doors. It is designed to improve oil cleanliness and to increase the Filter Insert life of Wash Oil Filters. The CJC PSi® Filter Insert has a large dirt holding capacity and removes all four contamination types in the same process: particles, water, acidity and varnish. The CJC® PSi Filter Insert is designed for systems with high flow. The CJC® PSi Filter Insert is used in CJC® Wash Oil Filters within the CJC® Fine Filter HDU series.

Used for the maintenance of the below oil types:

- Wash oil for steel pressing and stamping

CONTAMINATION CAPACITIES

Based on field experience we have observed that the total Dirt Holding Capacity (DHC) is dependent on the shape and density of particles and other variables within an oil system.

When saturated, the total weight of accumulated contamination depends on the application, the combination of contaminants, as well as the density and shape of the captured contamination.

Contamination Capacities	Size
	27/27
Solids, kg / lb	4 / 8.8
Varnish, kg / lb	4 / 8.8

COMPONENTS

CJC® Filter Inserts consist of cellulose bonded discs **made of 100% natural cellulose fibres from sustainable resources; no plastic, no metal, no chemicals.**



DISPOSAL OF USED CJC® FILTER INSERTS

CJC® Oil Filters are green solutions, and at C.C.JENSEN one of our objectives is caring for the environment. Therefore, please arrange for proper disposal of used filter inserts in accordance with your own local legislation.

IDENTIFICATION

To order the CJC PSi® Filter Inserts, please use:

Article No.:


- 1 x PSi 27/27: PA5601375



PSi 27/27

FILTRATION TECHNOLOGIES

- ▶ **Oil filtration degree**
*Particles can be removed as shown in the illustration below *)*
For wash oil filtration, the dirt holding capacity of the filter insert is paramount in order to reduce operation costs. Our focus is on removing the smallest particles, which create dents and cracks in the sheet metal.
- ▶ **Oxidation and oil degradation products**
The cellulose material retains oxidation by-products, resins, sludge, and varnish. The huge surface area of the filter media removes contamination through absorption and adsorption. By effectively removing contaminants we can slow down the rate of oil degradation.
- ▶ **Water resistancy**
AA Filter Inserts are designed not to block by water. After the initial absorption of some water, the filter insert will allow water to pass through without increasing the differential pressure.
- ▶ **Acidity stabilisation**
Acidity is a natural part of the oil degradation process and will be retained by the CJC® Filter Insert using the absorption technology.



BENEFITS in general

C.C.JENSEN DEPTH FILTER EFFICIENCY TEST

CJC® Filter Inserts are designed to last for one year, therefore testing of a high density depth filter for a few hours does not make sense. The C.C.JENSEN test is inspired by a modified ISO 16889, using finer test dust (UFTD), which resembles real dust and wear particles better than the coarse MTD test dust used in the standard Multi-pass test - designed for thin pleated filter media. The test modification also includes a much longer test time to get close to a real-life application scenario. The main advantage of CJC® Filter Inserts is the huge surface area, which distributes the oil flow and particles evenly and ensures stable low velocity for optimum retention of contamination. The large filter mass makes this unmatched high dirt holding capacity possible.


DIRT HOLDING CAPACITY CREATES VALUE

Competitive Filter Insert costs divided by dirt holding in kg:

3-micron filtration	Example 1	Example 2
Filter Insert type	Competitive pleated filter	CJC® cellulose depth media
Cost of element vs. Filter Insert	1 x €	4 x €
Dirt holding capacity	0.100 kg	4 kg
Cost per kg removed contamination	10 x € per kg	1 x € per kg

SLOW DOWN OIL AGEING

By removing all four contamination types (particles, water, acidity, and varnish), the CJC® Filter Inserts can slow down the oil ageing process and prolong the oil lifetime (see ill. 1). CJC® often results in 2-5 times longer oil lifetime, leading to considerable savings and reduction of CO₂ emissions. Field experiences show that removing particles of 3 µm and below with CJC® Filter Inserts has a significant effect on oil and component lifetime.



YOUR BENEFITS WITH CJC®

CJC® Filter Inserts have the highest dirt holding capacity on the market due to special cellulose-based material. Furthermore, the unique construction of the bonded discs, creates a large filtration area (see ill. 2) resulting in reduced costs of ownership. The CJC® Filter Inserts are a modular design, which allows them to fit any applications and requirements.

1. The CJC® Filter Insert features:

- a. Depth media of moulded cellulose.
- b. Highest Dirt Holding Capacities (DHC).
- c. **100% natural cellulose fibres from sustainable resources; no plastic, no metal, no chemicals.**



2. Removal of contaminants, 4-in-1:


- a. **Particles:**
Lifetime of both oil and component are increased considerably.
- b. **Oil degradation products:**
Avoid sticking valves, lacquering, and varnish on metal surfaces.
- c. **Water:**
Reduce the risk of micro-pitting, bacterial growth, sludge etc.
- d. **Acidity/TAN:**
Reduce oil ageing and wear on equipment.

3. OEM requirements

Experience and application knowledge of C.C.JENSEN ensure that CJC® solutions can meet specifications from OEMs on oil cleanliness.

All helping to minimise further degradation of the oil.

CJC® DEPTH FILTRATION EFFICIENCY



ill. 2)

This graphic describes the technology and the efficiency of depth Filter Inserts removing contaminants by adsorption & absorption.

MAINTENANCE RECOMMENDATIONS

To achieve the highest possible oil cleanliness level, the CJC® Filter Inserts need to be changed at least once a year. Because of accumulated oil degradation products (oxidation, acids, and varnish) no matter what the pressure gauge indicates the used Filter Inserts should be replaced annually. Leaving filter media in service for longer than one year will result in decreased oil filtration efficiency and increased risk of breakdowns and component wear.

